


DECLARATION OF PERFORMANCE
according to Regulation (EU) 305/2011
0667I - RPC - 29/10/2024

1. Unique identification code of the product type: **TERAMO 17 PLUS** P64467X (Invicta) - 72460538XXI (Caminetti Montegrappa)
Residential space heating appliance fired by wood pellets with hot water supply
EN 14785:2006.
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11, section 4:
TERAMO 17 PLUS
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Residential space heating appliance fired by wood pellets with hot water supply
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11, section 5:
Brand: **INVICTA** Manufacturer: **CAMINETTI MONTEGRAPPA S.p.A. con Socio Unico**
Zone Industrielle lieu-dit « la gravette » **Via A. da Bassano, 7/9**
08350 DONCHERY - FRANCE **36020 POVE DEL GRAPPA - ITALIE**
Tél: +33 0324 277171 **Tél: +39 0424 800500**
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3 and 4
6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified laboratory Kiwa Italia S.p.A. (NB 0476) performed the determination of the product type on the basis of type testing under system 3 and issued test report
3013197 dated 28/10/2024

7. Declared performance

Harmonized technical specification	EN 14785:2006.			
Essential Characteristics	Performance			
Fire safety				
Reaction to fire	A1			
Distance to combustible materials (please see detailed information in the manual)	Minimum distances, in mm:			
	rear	200	floor	0
	sides	200	ceiling	0
	front	1500		
Risk of burning fuel falling out	Pass			
Emission of combustion products		at nominal heat output	at reduced heat output	
	CO (13% O ₂)	0,0038 %	0,0045 %	
	PM	15 mg/Nm ³	19 mg/Nm ³	
Surface Temperature	Pass			
Electrical safety	Pass (EN 60335-2-102:2016)			
Cleanability	Pass			
Maximum operating pressure	3 bar			
Flue gas temperature at nominal heat output	T 98°C			
Mechanical resistance (to carry a chimney/flue)	NPD			
Nominal heat output	17,2 kW			
Room heating output	3,2 kW			
Water heating output	14,0 kW			
Energy efficiency	at nominal heat output		at reduced heat output	
	94,3%		96,1%	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by				Signature 
Contact Person	Function	Date	Place	
ing. Andrea Tezza	Technical Manager	29/10/2024	Pove del Grappa	