

DECLARATION OF PERFORMANCE

according to Regulation (EU) 305/2011

0661I - RPC - 03/07/2024

1. Unique identification code of the product type: **VIESTE 7 PLUS**

P64466X (Invicta) - 72410544XXI (Caminetti Montegrappa)

Residencial space heating appliance fired by wood pellets without hot water supply

EN 14785:2006

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11, section 4:

VIESTE 7 PLUS

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Residencial space heating appliance fired by wood pellets without hot water supply

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11, section 5:

Brand:

Manufacturer:

INVICTA

Zone Industrielle lieu-dit « la gravette »
08350 DONCHERY - FRANCE
Tél: +33 0324 277171

CAMINETTI MONTEGRAPPA S.p.A. con Socio Unico Via A. da Bassano, 7/9 36020 POVE DEL GRAPPA - ITALIE Tél: +39 0424 800500

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 and 4

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified laboratory Kiwa Italia S.p.A. (NB 0476) performed the determination of the product type on the basis of type testing under system 3 and issued test report

2013264 dated 02/07/2024

7. Declared performance

Harmonized technical specification	EN 14785:20	06								
Essential Characteristics	Performance									
Fire safety										
Reaction to fire	A1									
	Minimum distances, in mm:									
Distance to combustible materials	rear 200			floor -						
(please see detailed information in the manual)		sides	200		ceiling	-				
		front	1500							
Risk of burning fuel falling out	Pass									
Emission of combustion products		at nominal heat output		at reduced heat output						
	CO (13% O ₂)	0,0093 %		0,0112 %						
	PM	15 mg/Nm³		19 mg/Nm³						
Surface Temperature	Pass									
Electrical safety	Pass (EN 60335-2-102:2016)									
Cleanability	Pass									
Maximum operating pressure	- bar									
Flue gas temperature at nominal heat output	T 169°C									
Mechanical resistance (to carry a chimney/flue)	NPD									
Nominal heat output	7,3 kW									
Room heating output	7,3 kW									
Water heating output	- kW									
Energy efficiency	at nominal heat ouput			at reduced heat ouput						
	88,8%			92,3%						

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by			Signature	Y	
Contact Person	Function	Date	Place	\bigcap 1	
ing. Andrea Tezza	Technical Manager	03/07/2024	Pove del Grappa	maren	LM/